

# MATERIAL SAFETY DATA SHEET

ELJEN TECHNOLOGY  
SWEETWATER, TX 79556

Emergency Phone (24 hours)  
CHEMTREC (800) 424-9300

Page: 1 of 5  
Date: 16 July 2010

**PRODUCT NAME: EJ-301 LIQUID SCINTILLATOR**

## SECTION I SUPPLIER INFORMATION

**COMMON NAME** EJ-301  
**CHEMICAL NAME** Aromatic hydrocarbon + organic fluors  
**FORMULA** C<sub>6</sub>H<sub>4</sub>(CH<sub>3</sub>)<sub>2</sub>  
**PRODUCT CAS #** 1330-20-7  
**MANUFACTURER** ELJEN TECHNOLOGY  
**ADDRESS** 1300 W. BROADWAY  
SWEETWATER, TEXAS 79556  
**PHONE** (325) 235-4276  
**FAX** (325) 235-0701

## SECTION II HAZARDOUS INGREDIENT INFORMATION

COMPONENT	% WT.	OSHA-PEL	TLV-ACGIH
Aromatic hydrocarbon	> 90%	435 mg/m <sup>3</sup>	435 mg/m <sup>3</sup>
Organic fluors	<10%	not determined	not determined

### INGREDIENT HAZARD STATEMENT

Solvent is flammable and toxic.

Solvent is harmful by inhalation, in contact with skin and if swallowed.

Solvent is irritating to the eyes, respiratory system and skin.

## SECTION III PHYSICAL/CHEMICAL PROPERTIES

**BOILING POINT** 137-144°C (285°F)  
**MELTING POINT** Not applicable  
**SPECIFIC GRAVITY (H<sub>2</sub>O=1)** 0.87  
**VAPOR PRESSURE (mm Hg)** 18 mm @ 37.7°C (100°F)  
**VAPOR DENSITY (air =1)** 3.7  
**PERCENT VOLATILE BY VOLUME (%)** 99%  
**EVAPORATION RATE (Ether=1)** 9.5  
**SOLUBILITY IN WATER** Nil

**APPEARANCE AND ODOR** Clear, blue fluorescent liquid with aromatic odor

# MATERIAL SAFETY DATA SHEET

ELJEN TECHNOLOGY  
SWEETWATER, TX 79556

Emergency Phone (24 hours)  
CHEMTREC (800) 424-9300

Page: 2 of 5  
Date: 16 July 2010

**PRODUCT NAME: EJ-301 LIQUID SCINTILLATOR**

## SECTION IV FIRE AND EXPLOSION HAZARD DATA

**FLASH POINT (Method used):** 85°F (29°C) (cc)

**AUTO-IGNITION TEMP:** 932°F (500°C)

**FLAMMABLE LIMITS**

**LEL** 1.1%

**UEL** 7%

**EXTINGUISHING MEDIA:**

Carbon dioxide, dry chemical powder, alcohol or polymer film  
Water may be effective for cooling but may not extinguish flames.

**SPECIAL FIRE FIGHTING PROCEDURES:**

Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes.

Use water spray to cool fire-exposed containers.

**UNUSUAL FIRE AND EXPLOSION HAZARDS:**

Vapor may travel considerable distance to ignition source and flash back.  
Forms explosive mixtures in air.

## SECTION V REACTIVITY DATA

**STABILITY:** STABLE  UNSTABLE

**CONDITIONS TO AVOID:** Sources of sparks (welding).

**INCOMPATIBILITY(Mat's. To Avoid):** Oxidizing agents

**HAZARDOUS DECOMPOSITION PRODUCTS:** Toxic combustion products,  
Carbon dioxide, Carbon monoxide

**HAZARDOUS POLYMERIZATION:** Will not occur.

**AVOID:** Not applicable

# MATERIAL SAFETY DATA SHEET

ELJEN TECHNOLOGY  
SWEETWATER, TX 79556

Emergency Phone (24 hours)  
CHEMTREC (800) 424-9300

Page: 3 of 5  
Date: 16 July 2010

**PRODUCT NAME: EJ-301 LIQUID SCINTILLATOR**

## SECTION VI HEALTH HAZARD DATA

### ROUTES OF ENTRY

**EYES:** Yes  
**SKIN:** Yes  
**INHALATION:** Yes  
**INGESTION:** Yes

### ACUTE EFFECTS OF OVEREXPOSURE

**EYE:** Can cause severe irritation, redness, tearing, blurred vision.

**SKIN:** Prolonged or repeated contact can cause moderate irritation, defatting, and dermatitis.

**INHALATION:** May cause irritation to upper respiratory tract. Excessive breathing can cause dizziness, nausea, headache.

**INGESTION:** May cause gastrointestinal disturbances, nausea, vomiting and diarrhea.

**CARCINOGENICITY:** Not determined

**NTP:** Not applicable      **IARC:** Not applicable      **OSHA:** Not applicable

**CHRONIC HEALTH HAZARD:** Long term exposure can lead to damage to liver, kidneys and nerves. Possible reproductive disorders based on tests of the solvent base with animals.

### MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

Not determined

### EMERGENCY FIRST AID

**EYE** Immediately flush eyes with copious amounts of water for at least 15 minutes, lifting upper and lower lids. Contact physician.

**SKIN CONTACT:** Immediately wash with copious amounts of soap and water. Remove contaminated clothing and launder for reuse. Contact physician if irritation and inflammation persists.

**INHALATION:** Remove to fresh air. If not breathing, give artificial respiration. Call a physician.

**INGESTION:** Do not induce vomiting. Call a physician. Aspiration solvent base into lungs by vomiting can lead to fatal complications.

# MATERIAL SAFETY DATA SHEET

ELJEN TECHNOLOGY  
SWEETWATER, TX 79556

Emergency Phone (24 hours)  
CHEMTREC (800) 424-9300

Page: 4 of 5  
Date: 16 July 2010

**PRODUCT NAME: EJ-301 LIQUID SCINTILLATOR**

## SECTION VII HANDLING PRECAUTIONS

**EPA WASTE #:** U239                      **HAZARD CLASS:** 3  
**UN #:** 1993                              **PACKING GROUP:** III  
**DOT CLASSIFICATION:** Flammable Liquid N.O.S. (Xylene)  
**LABELS REQ'D:** Class 3, Flammable Liquid

### IN CASE OF RELEASE OR SPILLAGE

Evacuate area. Shut off all sources of ignition. Cover with an activated carbon absorbent. Take up and place in closed containers. Ventilate and wash spill site after pick-up is completed. Absorb in vermiculite or other floor absorbent.

### WASTE DISPOSAL METHOD

Burn in a chemical incinerator. Observe all Federal, state and local laws.

### HANDLING AND STORAGE

Use non-sparking tools. Keep containers tightly closed. Keep away from heat and open flames. Do not keep empty containers.

## SECTION VIII SPECIAL PROTECTION / CONTROL MEASURES

### RESPIRATORY PROTECTION

Wear appropriate NIOSH/MSHA approved respirator.

### VENTILATION

Mechanical exhaust required. Fumes are heavier than air.  
Do not breathe the vapor

### SKIN PROTECTION

Chemical resistant gloves and clothing. Solvent base is readily absorbed through skin.

### EYE PROTECTION

Chemical resistant and flash protective goggles.

### WORK HYGIENE PRACTICES

Wash thoroughly with soap and water after handling.

# MATERIAL SAFETY DATA SHEET

ELJEN TECHNOLOGY  
SWEETWATER, TX 79556

Emergency Phone (24 hours)  
CHEMTREC (800) 424-9300

Page: 5 of 5  
Date: 16 July 2010

**PRODUCT NAME: EJ-301 LIQUID SCINTILLATOR**

## SECTION IX ADDITIONAL INFORMATION

### SARA HAZARD CATEGORIES

IMMEDIATE (ACUTE) HEALTH HAZARD: YES  NO

DELAYED (CHRONIC) HEALTH HAZARD: YES  NO

FIRE HAZARD: YES  NO

REACTIVITY HAZARD: YES  NO

SUDDEN RELEASE OF PRESSURE: YES  NO

### SARA SECTION 313 NOTIFICATION

THIS PRODUCT MAY CONTAIN A TOXIC CHEMICAL (OR CHEMICALS)  
SUBJECT TO SARA SECTION 313 REPORTING REQUIREMENTS.

<u>CHEMICAL NAME</u>	<u>CAS #</u>	<u>EC #</u>	<u>%WT</u>
Xylene	1330-20-7	215-535-7	> 90%

### EUROPEAN INFORMATION

EC Index No: 601-022-01-6  
Flammable; Toxic; R 10, Flammable.  
R 20/21, Harmful by inhalation and in contact with skin.  
R38. Irritating to skin.  
S25, Avoid contact with eyes.

Information presented herein has been compiled from sources considered to be dependable, and is accurate and reliable to the best of our knowledge and belief, but is not guaranteed to be so. Since conditions of use are beyond our control, we make no warranties, expressed or implied, except those that may be contained in our written contract of sale or acknowledgment.